

1 **In the Claims:**

2 | Claim 1 (currently amended)

3 A sealing member adapted to be mounted in between a cab and a canopy where
4 the cab has a rear window with a perimeter sub-region and the canopy has a
5 forward window providing a perimeter sub-region where the perimeter sub-
6 regions of the rear window and the forward window are substantially aligned, the
7 sealing member comprising:

8 an elongate axis and a first set of opposed elongated surfaces comprising
9 a first surface and a second surface whereby the first and second surfaces
10 are adapted to engage the perimeter sub-regions of the rear window and
11 the forward window, the elongate member further having a second set of
12 opposed surfaces comprising a third elongated surface and a fourth
13 surface that are substantially opposed to one another and are adapted to
14 simultaneously engage the perimeter sub-region of the rear window and
15 the perimeter sub-region of the forward window, where a sealing body
16 width is defined between the first and second surfaces that is a greater
17 distance than a sealing body thickness that is defined as the distance
18 between the third and fourth surfaces,
19 whereas the elongate member is adapted to rotate substantially about its
20 central elongate axis to provide engagement with the first and second
21 opposed surfaces to the perimeter sub-regions of the rear window and the
22 forward window or to provide engagement of the third and fourth opposed
23 surfaces to the perimeter sub-regions of the rear window and the forward
24 window where a combination of the engagement of the first and second

1 opposed surfaces along a portion of the perimeter sub-region and the
2 engagement of the third and fourth surfaces along another portion of the
3 perimeter sub-region maintains a substantial seal between the cab and
4 the canopy.

5
6 Claim 2 (currently amended):

7 A elongate member adapted to be mounted between a cab and a canopy where
8 the cab has a rearward window with a perimeter sub-region and the canopy has
9 a forward window having a perimeter sub-region where the rearward and forward
10 windows have a first lateral perimeter sub-region, a second lateral perimeter sub-
11 region, and a lower perimeter sub-region and upper perimeter sub-region, the
12 elongate member having the properties:

13 made from flexible material that is adapted to compress at a first rate and
14 expand to an original cross sectional size at a second rate which is slower
15 than said first rate whereby the elongate member is adapted to compress
16 and frictionally engage between the first lateral perimeter sub-region, the
17 upper perimeter sub-region, the second lateral perimeter ~~sub-region in~~
18 sub-region and the lower perimeter sub-region and after said engagement
19 the material has compression memory where the expansion rate is further
20 impeded and the pressure upon the first lateral perimeter sub-region, the
21 second lateral perimeter sub-region, the upper perimeter sub-region and
22 the lower perimeter sub-region and upper perimeter sub-region is reduced
23 than ~~before~~ before the compression memory has set in where the

1 elongate member has a central elongate axis and first and second
2 surfaces that are substantially opposed to one another and have a first
3 sealing member distance between the first and second surfaces and third
4 and fourth surfaces that are substantially opposed to one another and
5 have a second sealing member distance between the third and fourth
6 surfaces where a combination of the engagement of the first and second
7 opposed surfaces along a portion of the perimeter sub-region and the
8 engagement of the third and fourth surfaces along another portion of the
9 perimeter sub-region maintains a substantial seal between the cab and
10 the canopy.
11

12 Claim 3 (cancelled):
13

14 Claim 4 (previously presented):

15 The elongate member as recited in claim 2 where the first and second lateral
16 perimeter sub-regions have a lateral longitudinal distance between the rearward
17 perimeter sub-region and the forward perimeter sub-region and the upper
18 perimeter sub-region has a lateral longitudinal distance between the rearward
19 perimeter sub-region and the forward perimeter sub-region whereby the lateral
20 longitudinal distance is not the same as the upper longitudinal distance whereby
21 the elongate member is adapted to rotate about the central elongate axis
22 whereby the first and second surfaces are adapted to engage the first and

1 second lateral perimeter sub-regions and the third and fourth surfaces are
2 adapted to engage the upper perimeter sub-region.
3

4 Claim 5 (previously presented):

5 The elongate member as recited in claim 4 whereby the lower perimeter sub-
6 region has a longitudinal distance between the rearward perimeter sub-region
7 and the forward perimeter sub-region and the third and fourth surfaces of the
8 sealing member are adapted to engage the lower perimeter sub-region.
9

10 Claim 6 (previously presented):

11 The elongate member as recited in claim 5 where the sealing member has a first
12 end and a second end whereby the first and second ends are adapted to engage
13 one another in a face-to-face engagement in between the rearward perimeter
14 sub-region and the forward perimeter sub-region.
15

16 Claim 7 (currently amended):

17 The elongate member as recited in ~~claim 3~~ claim 2 where the lateral regions are
18 located on movable window sections of the forward window and the rearward
19 window.
20

21 Claim 8 (currently amended):

1 The elongate member as recited in ~~claim 4~~ claim 2, where the lateral regions are
2 located on fixed window portions of the forward window and the rearward
3 window.

4
5 Claim 9 (currently amended):

6 A method of sealing the gap between the perimeter sub-region of any rearward
7 window having rearward perimeter sub-region of a cab of a truck and a forward
8 window having a forward perimeter sub-region of a canopy attached to the bed of
9 a truck, the distance between the rearward perimeter sub-region in the forward
10 perimeter sub-region defines a promoter gap having any longitudinal distance
11 that can vary with respect to position along the promoter region, the method
12 comprising the steps of:

13 retrieving an elongate member having a central elongate axis and being
14 comprised of a foam-like material that is adapted to compress at a first
15 rate and held at a compressed position to invoke compression memory
16 and expand at a second rate that is substantially lower than said first rate,
17 the elongate member having first and second surfaces that are
18 substantially opposed to one another and third and fourth surfaces that
19 are substantially opposed to one another, positioning the elongate
20 member along the perimeter sub-region whereby the elongate member
21 engages the rearward perimeter sub-region and the forward perimeter
22 sub-region with either the first and second surfaces or the third and fourth
23 surfaces depending upon the longitudinal distance of the perimeter gap

1 where a combination of the contact of the first and second opposed
2 surfaces along a portion of the perimeter sub-region and the contact of the
3 third and fourth surfaces along another portion of the perimeter sub-region
4 between the cab and the canopy maintains a substantial seal between the
5 cab and the canopy.
6

7 Claim 10 (currently amended):

8 An elongate member for use in filling a perimeter sub-region between a cab rear
9 wall and a canopy forward wall capable of keeping out debris to keep out dirt
10 ~~or the like~~ where the elongate member having properties comprised of:

11 a compression memory having a compression memory rate of expansion
12 and a fast compression rate, a cross sectional form with a width dimension
13 substantially greater than the thickness dimension, an adaptability to
14 rotate the sealing body about an elongate axis which enables the sealing
15 body to fill the gap as required where the combination of the surfaces of
16 the sealing body and various widths engaging the perimeter sub-region
17 between the cab rear wall and the canopy forward wall maintains a
18 substantial seal there between,
19 said elongate member having a support system having an outward
20 expansion force and a vertical frictional force, the sealing body being held
21 in a stationary position through the combination of the outward expansion
22 force and the vertical frictional force in the perimeter sub-region where the
23 compression memory rate of expansion provides a minimal force to

transfer between the cab wall and the canopy wall, whereby substantially avoiding abrasion of a particle of dirt or the like between the sealing body and the cab or canopy walls.

Claim 11 (original):

The sealing body of claim 10 including a rate of expansion that is substantially slow enough that after compression, the body will not re-expand to its former shape for a period of hours.

Claim 12 (cancelled):

Claim 13 (cancelled):

Claim 14 (original):

The sealing body of claim 10 including a cross section shape that is substantially square.

Claim 15 (currently amended):

A method of sealing a gap between a cab back wall and a canopy front wall where the gap to be sealed has non-uniform distance from the cab back wall and a canopy front wall, the method comprising the steps of:

retrieving an elongate member having a central axis and a wide portion with a wider cross-sectional portion-distance greater than a narrow portion narrow-cross sectional portion where the narrow portion the and wide portion exist on the same cross-sectional plane.

1 placing the elongate member in a perimeter gap region therein between
2 the front cab and the back canopy, the perimeter gap region,
3 rotating the elongate member about its central axis so as to accommodate
4 the various gap widths between the back cab and canopy front wall,
5 fitting the elongate member into the gap such ~~that wide~~ that the wide
6 portion of the body is placed in the large portion of the gap and the thin
7 portion of the body is placed in the small portions of the gap so both the
8 wide portion and the thin portion of the body engage the non-uniform
9 distance from the cab back wall and a canopy front wall,
10 expanding the elongate member to substantially the width distance
11 between the canopy front wall and the vehicle back cab wall along the gap
12 region,
13 supporting the elongate member in a stationary position where the sealing
14 body has an outward expansion force and a vertical frictional force, the
15 combination of the forces being enough to support the sealing body's
16 stationary position.

17
18 Claim 16 (original):

19 The method as recited in claim 15 whereby the vehicle back cab has a painted
20 surface.

21
22 Claim 17 (original):

1 The method as recited in claim 16 whereby the elongate member has a slow
2 memory and rate of expansion provides a sufficiently low force to prevent debris
3 to scratch the surfaces of the cab.

4

5 Claim 18 (original):

6 The method as recited in the claim 15 whereby the sealing body is adapted to
7 extend into cavity regions of the perimeter portion of the window frame and
8 frictionally engage therein.

9

10 Claim 19 (original)

11 The method as recited in the claim 15 above whereby the sealing body is
12 adapted to extend into the cavity regions of a perimeter portion of a window
13 frame and provide a circuitous route for dust and debris to break the seal
14 between the cab region and the surrounding environment.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.